

LU500

The Ultimate Lightweight Unit for Professional Newsgathering



Powered by LiveU's multi-processor video encoding engine and weighing around 1 kg (2.2 lbs), LU500 represents the ultimate uplink device for professional newsgathering. With its proprietary internal antenna, the LU500 optimizes available bandwidth to deliver broadcast-quality, resilient live HD video transmission for 24/7 news and events coverage on-the-move and in fixed locations.

The LU500 combines high performance and portability with an end-to-end boot-up time of less than one minute. The unit supports Anton Bauer, V-Lock, PAG, and LiveU's internal swappable batteries and offers advanced remote control functions via the LiveU Central management platform.

LU500, with the new multi-media processors, offers up to ten bonded connections plus WiFi and two LAN connections. The unit can be connected to the LiveU Xtender external antenna for extra-resiliency in challenging conditions, and connected to satellite equipment to create a hybrid cellular/satellite solution for guaranteed bandwidth in remote areas. The LU500 can also support additional optional modems via external USB ports.

The LU500 can be controlled by a single operator in the field using an intuitive touch-screen interface or controlled remotely from any computer using the LiveU Central management platform.

LU500 Technical Specifications

PRODUCT	INTEGRATED UNIT	Audio / video encoder, micro SD card, cellular & wireless modems, internal battery
	PORTABILITY	Custom design, professional-grade backpack
VIDEO INPUT	RESOLUTIONS	1080p50/60/25/30/24, 1080i50/60, 720p50/60/25/30, PAL, NTSC
	HW INTERFACES	SDI, HDMI
	VIDEO FORMATS	3G/HD/SD-SDI, HDMI 1.4, full A/V auto detection
AUDIO/VIDEO ENCODING	VIDEO ENCODER	H.264 AVC high profile
	AUDIO ENCODER	AAC-LC
	VIDEO TRANSPORT	RTP
INTEGRATED BONDED INTERFACES	SIMULTANEOUS BONDING	Up to 13 network links; inc. 6-8 x integrated 4G LTE / 3G cellular or WiMAX modems + internal Wi-Fi and 2 Ethernet ports
	SUPPORTED TECHNOLOGIES	4G LTE, HSPA+, HSUPA, HSDPA, UMTS, CDMA EVDO Rev 0/A/B, Mobile WiMAX, and internal Wi-Fi 802.11 a,b,g & n support
PROPRIETARY RF TECHNOLOGY	ANTENNA ARRAYS	Benefits in video quality, resiliency, coverage, operation in areas of poor coverage, on-the-drive, and even in crowded areas. Enhanced support for all common wireless frequencies including LTE
OPERATIONAL MODES	MULTI-PROFILE SELECTION	Low latency mode Maximum Quality mode for increased compensation in noisy networks
	MULTI-TARGET OUTPUT	Diverse A/V output through SDI and H.264 streams including connectivity for CDNs
POWER	POWER SOURCES	Integral battery: 3 hours Vehicle Lighter input: 12VDC AC: 100V to 240V
USER INTERFACE	LOCAL CONTROL	Full monitoring and control using touch-screen UI
	REMOTE CONTROL	Full web-based remote control from laptops, or Google Chrome based browsers
	PREVIEW	Video preview; per-network cellular connectivity status incl. throughput, network delay etc.
RICH FEATURE SET	RESILIENCY AND QUALITY	Top video quality and resiliency through algorithms such as automatic Adaptive Bit Rate (ABR). Video encoding bit rate is set automatically; automatic Forward Error Correction (FEC) and other lost packet recovery algorithms to maximize Quality of Experience for the end-user
	PROFESSIONAL FEATURES	Low latency for studio interviews; Store & Forward; file transfer (FTP); video and audio indicators; under one minute boot-up time; and the ability to control the unit from its touch screen, the server or from any web enabled device
PHYSICAL & INTERFACES	DATA	Micro SD Card Slot, Micro USB 2.0 OTG, RJ-45 Ethernet, Audio jack (in + out)
	DIMENSIONS	With 3hr battery: 150mm x 225mm x 70mm / 5.9" x 8.8" x 2.7" (W x H x D)
	WEIGHT	1.08kg (38oz) without battery, 1.68kg (59oz) with 3 hr battery
	TEMPERATURE	Operating: -5C to +45C (23F to 113F)

LiveU Inc.
 2 University Plaza, Suite 505, Hackensack,
 New Jersey 07601, USA
 Tel: 1-(201)-742-5228
 US & Americas: info_us@liveu.tv
 International: info@liveu.tv